

WAIN-ROY®

JAW™

BUCKET

BEYOND RUGGED

Our hydraulically operated Wain-Roy® brand multi-purpose Jaw™ bucket is designed for extreme-duty applications. Available for backhoes and excavators to 45,000 pound machine weight, the Jaw bucket can pin directly to your machine or you can leverage the speed and efficiency of the Wain-Roy rigid or Swinger™ coupler system.

Advantages


- Curved side leading edges, made of high-strength steel enable the Jaw bucket to cradle or clamp objects and rotate them throughout the normal bucket arc.
- Heat treated pins and bushings at all pivot joints for improved wear resistance.
- Jaw clamping force has up to 8,700 lbs. depending on bucket size and machine hydraulic pressure.
- Designed for easy maintenance—all grease fittings are in easy to access locations.
- Jaw cylinder rod's hard chrome plating and case hardening are three times deeper than industry standard.
- Cylinder guard isolates cylinder from materials in bucket.

PERFORMANCE GUIDE

Ideal for concrete removal, picking and placing boulders, removing stumps, clearing debris, and other trenching, clamping or clamshelling operations.

WainRoy®

WAIN-ROY® JAW™ BUCKET



SPECIFICATIONS

Machine weight class	1/4 yd. rated backhoes & excavators 11,000 – 16,000 lbs.	1/2 yd. rated backhoes & excavators 16,000 – 30,000 lbs.		3/4 yd. rated excavators 31,000 – 45,000 lbs.
Bucket widths	24"	24"	30"	36"
Heaped capacities	7.5 cu. ft.	10.6 cu. ft.	14.0 cu. ft.	20.0 cu. ft.
	0.28 cu. yd.	0.39 cu. yd.	0.52 cu. yd.	0.74 cu. yd.
Jaw clamp opening width	41"	51"	51"	51"
Approximate weight	650 lbs.	875 lbs.	975 lbs.	1,800 lbs.
Clamping force at 3,000 psi	5,872 lbs.	7,021 lbs.	7,021 lbs.	8,681 lbs.

Enhance your performance with Wain-Roy Jaw attachments.

JAW ATTACHMENTS

Unit	Machine class	Machine weight	Unit weight
	1/4 yd.	11,000 – 16,000 lbs.	180 lbs.
	1/2 yd.	16,000 – 30,000 lbs.	275 lbs.
	3/4 yd.	31,000 – 45,000 lbs.	275 lbs.
	1/4 yd. (5 ft.)	11,000 – 16,000 lbs.	180 lbs.
	1/2 yd. (6 ft.)	16,000 – 30,000 lbs.	459 lbs.
	3/4 yd. (6 ft.)	31,000 – 45,000 lbs.	459 lbs.

Contact our sales and service representatives today at 1-800-848-3447, option 1, or email to ConstructionInfo@WoodsEquipment.com.

Woods Equipment Company 2606 South Illinois Route 2, PO Box 1000, Oregon, Illinois 61061 tel 800-848-3447 www.WoodsEquipment.com

Warning! Some images may show safety shields removed to provide a better view. Equipment should never be operated with any safety shield removed. Some machines in this brochure may be shown with optional equipment. Always operate machines in accordance with supplied operator's manuals. ©2005 Woods Equipment Company. All rights reserved. WOODS, the Woods logo, "Tested. Proven. Unbeatable.", Wain-Roy, and Jaw are trademarks of Woods Equipment Company. All other trademarks, trade names, or service marks not owned by Woods Equipment Company that appear in this brochure are the property of their respective companies or mark holders. Specifications subject to change without notice. F-024 (Rev. 7/05)

WOODS
Woods Equipment Company